

EBONITE - Plutonium 2239



Oil Pattern Distance **Forward Oil Total Tank Configuration**

39 16.76 mL N/A **Reverse Brush Drop Reverse Oil Total Tank A Conditioner**

39 9.9 mL **Terrain** Oil Per Board **Volume Oil Total Tank B Conditioner**

Multi ul 26.66 mL **Fire**

2 5L 5R 1 50 14 B 31 7.9 9.8 1.9 155 3 6L 6R 1 50 14 B 29 9.8 11.7 1.9 145 4 8L 7R 1 45 14 B 26 11.7 13.6 1.9 117 5 10L 9R 2 45 14 B 44 13.6 17.5 3.9 198 6 12L 11R 1 40 18 B 18 17.5 20.0 2.5 72 7 13L 12R 1 40 18 B 16 20.0 22.5 2.5 64 8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0		START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
3 6L 6R 1 50 14 B 29 9.8 11.7 1.9 145 4 8L 7R 1 45 14 B 26 11.7 13.6 1.9 117 5 10L 9R 2 45 14 B 44 13.6 17.5 3.9 198 6 12L 11R 1 40 18 B 18 17.5 20.0 2.5 72 7 13L 12R 1 40 18 B 16 20.0 22.5 2.5 64 8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	1	2L	2R	5	50	14	В	185	0.0	7.9	7.9	9250
4 8L 7R 1 45 14 B 26 11.7 13.6 1.9 117 5 10L 9R 2 45 14 B 44 13.6 17.5 3.9 198 6 12L 11R 1 40 18 B 18 17.5 20.0 2.5 72 7 13L 12R 1 40 18 B 16 20.0 22.5 2.5 64 8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	2	5L	5R	1	50	14	В	31	7.9	9.8	1.9	1550
5 10L 9R 2 45 14 B 44 13.6 17.5 3.9 198 6 12L 11R 1 40 18 B 18 17.5 20.0 2.5 72 7 13L 12R 1 40 18 B 16 20.0 22.5 2.5 64 8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	3	6L	6R	1	50	14	В	29	9.8	11.7	1.9	1450
6 12L 11R 1 40 18 B 18 17.5 20.0 2.5 72 7 13L 12R 1 40 18 B 16 20.0 22.5 2.5 64 8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	4	8L	7R	1	45	14	В	26	11.7	13.6	1.9	1170
7 13L 12R 1 40 18 B 16 20.0 22.5 2.5 64 8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	5	10L	9R	2	45	14	В	44	13.6	17.5	3.9	1980
8 2L 2R 0 40 18 B 0 22.5 24.0 1.5 9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	6	12L	11R	1	40	18	В	18	17.5	20.0	2.5	720
9 2L 2R 0 40 22 B 0 24.0 35.0 11.0	7	13L	12R	1	40	18	В	16	20.0	22.5	2.5	640
	8	2L	2R	0	40	18	В	0	22.5	24.0	1.5	0
10 21 2R 0 40 26 B 0 35.0 39.0 4.0	9	2L	2R	0	40	22	В	0	24.0	35.0	11.0	0
	10	2L	2R	0	40	26	В	0	35.0	39.0	4.0	0

	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	55	30	Α	0	39.0	30.0	-9.0	0
2	13L	12R	1	55	22	Α	16	30.0	26.9	-3.1	880
3	11L	10R	2	55	18	Α	40	26.9	21.8	-5.1	2200
4	9L	9R	1	55	18	Α	23	21.8	19.3	-2.5	1265
5	7L	7R	1	55	18	Α	27	19.3	16.8	-2.5	1485
6	2L	2R	2	55	14	Α	74	16.8	12.9	-3.9	4070
7	2L	2R	0	55	14	Α	0	12.9	0.0	-12.9	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



	01 71 401 400	01 401 401 400	401 471 401 407	401 400 470 400	401 400 400 00	40, 400 70 00	
Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R	
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside	
Track Zone Ratio	226	134	1	1	122	221	



