

BANK 3 MULTI M13



Oil Pattern Distance **Forward Oil Total Tank Configuration**

17.55 mL Multi Tank

42

Reverse Brush Drop Reverse Oil Total Tank A Conditioner

38 8.25 mL **FIRE** Oil Per Board **Volume Oil Total Tank B Conditioner**

50 ul 25.8 mL **TERRAIN**

1 2L 2R 3 14 A 111 0.0 3.9 3.9 5550 2 3L 3R 2 14 A 70 3.9 7.8 3.9 3500 3 4L 6R 1 18 A 31 7.8 10.3 2.5 1550 4 7L 9R 4 18 A 100 10.3 20.5 10.2 5000 5 11L 13R 1 22 A 17 20.5 23.6 3.1 850 6 14L 16R 2 26 A 22 23.6 30.9 7.3 1100 7 2L 2R 0 26 A 0 30.9 42.0 11.1 0		START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
3 4L 6R 1 18 A 31 7.8 10.3 2.5 1550 4 7L 9R 4 18 A 100 10.3 20.5 10.2 5000 5 11L 13R 1 22 A 17 20.5 23.6 3.1 850 6 14L 16R 2 26 A 22 23.6 30.9 7.3 1100	1	2L	2R	3	14	Α	111	0.0	3.9	3.9	5550
4 7L 9R 4 18 A 100 10.3 20.5 10.2 5000 5 11L 13R 1 22 A 17 20.5 23.6 3.1 850 6 14L 16R 2 26 A 22 23.6 30.9 7.3 1100	2	3L	3R	2	14	Α	70	3.9	7.8	3.9	3500
5 11L 13R 1 22 A 17 20.5 23.6 3.1 850 6 14L 16R 2 26 A 22 23.6 30.9 7.3 1100	3	4L	6R	1	18	Α	31	7.8	10.3	2.5	1550
6 14L 16R 2 26 A 22 23.6 30.9 7.3 1100	4	7L	9R	4	18	Α	100	10.3	20.5	10.2	5000
	5	11L	13R	1	22	Α	17	20.5	23.6	3.1	850
7 2L 2R 0 26 A 0 30.9 42.0 11.1 0	6	14L	16R	2	26	Α	22	23.6	30.9	7.3	1100
	7	2L	2R	0	26	Α	0	30.9	42.0	11.1	0

	START	STOP	LOADS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	В	0	42.0	35.0	-7.0	0
2	7L	7R	2	18	В	54	35.0	29.9	-5.1	2700
3	2L	2R	3	18	В	111	29.9	22.3	-7.6	5550
4	2L	2R	0	14	В	0	22.3	0.0	-22.3	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	1.8	1.17	1.02	1.07	1.27	2.05



